

ColorSpot 575E AT™

The ColorSpot 575E AT is an electronic ballast version of the ColorSpot 575 AT, which sees an expansion of features like flicker-free operation, enhanced light output, extended lamp life, power-saving mode for economy and reduced weight. The ColorSpot 575E AT is equipped with high practical large LCD graphic display. It also includes two separate gobo wheels and 2 separate colour wheels with the "SLOT & LOCK" system, motorized multi-step zoom with three different apertures of 15, 18 and 22 degrees; motorized iris, prism, separate and variable frost effects, remote focus and many, many more features.



Technical Specification

Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2
- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2

Optical system

- Dichroic glass reflector for maximising the light efficiency
- 15, 18 and 22 degree beam angles remotely adjustable
- Dichroic glass reflector for maximising the light efficiency
- 15, 18 and 22 degree beam angles remotely adjustable

Electrical specification and connections

- Wiring options: 100/120/208/230/240V, 50/60Hz
- Power consumption: 760VA at 230V/50Hz
- Wiring options: 100/120/208/230/240V, 50/60Hz
- Power consumption: 760VA at 230V/50Hz

Mechanical specification

- Height: 555 mm (21.9") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")
- Height: 555 mm (21.9") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")

Thermal specification

- Maximum ambient temperature: 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Maximum ambient temperature: 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

Rotating gobos

- Outside diameter - dichroic and glass gobos: 26.8 mm
- Image diameter - dichroic gobos: 22.0 mm
- Thickness - dichroic gobos: 1.1 mm (high temperature borofloat or better glass); glass gobos: max. thickness = 4 mm (high temperature borofloat or better glass)
- Outside diameter - dichroic and glass gobos: 26.8 mm
- Image diameter - dichroic gobos: 22.0 mm
- Thickness - dichroic gobos: 1.1 mm (high temperature borofloat or better glass); glass gobos: max. thickness = 4 mm (high temperature borofloat or better glass)

Control and programming

- Protocol: USITT DMX-512, RDM support
- Control channels: 19, 21, 27 or 29
- DMX channels: 4 protocol modes
- Protocol: USITT DMX-512, RDM support
- Control channels: 19, 21, 27 or 29
- DMX channels: 4 protocol modes

Electromechanical effects

- Motorized multi-step zoom with three different apertures (15°, 18°, 22°)
- Colour wheel 1: 9 dichroic filters + open
- Colour wheel 2: 8 replaceable "SLOT&LOCK" dichroic filters + open (including 3200K, correction filter and UV filter)
- Motorized multi-step zoom with three different apertures (15°, 18°, 22°)
- Colour wheel 1: 9 dichroic filters + open
- Colour wheel 2: 8 replaceable "SLOT&LOCK" dichroic filters + open (including 3200K, correction filter and UV filter)

Rigging

- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks
- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks

Optional accessories

- Remote Control IR
- Remote Control IR

Gobos&Colours

Rotating Gobo Wheel



15020153



15020152




15020151




15020150



15020149



15040011



15030017


Colour Wheel 1



14070054




14070052




14070041




14070045




14070043



14070051



14070040



14070039


Colour Wheel 2



14070047




14070048




14070043



14070045




14070041



14070049



14070046



14070042



14070044

Static Gobo Wheel



9/19/2024



ColorSpot 575E AT™





15010608



15010609



15010700



15010701



15010702



15010703



15010704



15010705



15010706