

ColorWash 2500E AT™

The ColorWash 2500E AT is newly equipped with a the Philips MSR Gold 1500 FastFit lamp, which makes it the most powerful Robe moving wash light fixture.



The ColorWash 2500E AT comes complete with CMY colour mixing system, variable CTO, 2 colour wheels and combined dimmer/shutter unit. The linear zoom has a range of 7° - 44°.

The ColorWash 2500E AT is an ideal tool for large live events and television shows and for all types of installations from multipurpose venues to large clubs.

Technical Specification

Source

- Standard Lamp: MSR 1500 FastFit
- Lamp on request: MSR GOLD 1200 FastFit
- Base: PGJX50
- Standard Lamp: MSR 1500 FastFit
- Lamp on request: MSR GOLD 1200 FastFit
- Base: PGJX50

Optical system

- High luminous glass reflector
- Zoom angle from 7° to 44°
- High luminous glass reflector
- Zoom angle from 7° to 44°

Electromechanical effects

- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%
- Cyan: 0-100%
- Magenta: 0-100%
- Yellow: 0-100%

Control and programming

- Protocol: USITT DMX-512, RDM support
- Control channels: 17, 21, 23, 24 and 30
- DMX channels: 5 protocol modes
- Protocol: USITT DMX-512, RDM support
- Control channels: 17, 21, 23, 24 and 30
- DMX channels: 5 protocol modes

Thermal specification

- Maximum ambient temperature (Ta): 40 °C (104 °F)
- Maximum surface temperature: 130 °C (266 °F)
- Maximum ambient temperature (Ta): 40 °C (104 °F)

- Maximum surface temperature: 130 °C (266 °F)

Electrical specification and connections

- Wiring options: 208/230/250 V, 50/60 Hz
- Power consumption: 1670 VA at 230 V/50 Hz
- Wiring options: 208/230/250 V, 50/60 Hz
- Power consumption: 1670 VA at 230 V/50 Hz

Mechanical specification

- Height: 641 mm (25.2 ") - head in horizontal position
- Width: 542 mm (21.3 ")
- Depth: 545 mm (21.5 ")
- Height: 641 mm (25.2 ") - head in horizontal position
- Width: 542 mm (21.3 ")
- Depth: 545 mm (21.5 ")

Rigging


- Mounting points: 8 pairs of ¼-turn locksFastening system: ROBE's own 2x Omega clamps
- Fixation option: Pan/Tilt-lock mechanism
- Mounting points: 8 pairs of ¼-turn locksFastening system: ROBE's own 2x Omega clamps
- Fixation option: Pan/Tilt-lock mechanism

Optional accessories


- Remote control IR
- Module of lens D200 PC
- Top Hats
- Remote control IR
- Module of lens D200 PC
- Top Hats

Gobos&Colours


Colour Wheel 1



14070268




14070269



14070270



14070271




14070272




14070273

Colour Wheel 2




14070121




14070174



14070175



14070176




14070177



14070179



14070178



14070182



14070181



14070183



14070180