

ColorWash 575 AT Zoom™

The ColorWash 575 AT Zoom includes all the features of the ColorWash 575 AT, and is enhanced with an extremely smooth linear motorized zoom that ranges from 8° to 50°. This is a great advantage, enabling the fixture a wider light output, making the ColorWash 575 AT Zoom suitable for all types of professional installations.



Technical Specification

Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2
- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2

Optical system

- High luminous-efficiency glass reflector
- Fresnel lenses of diameter 200 mm
- Internal diffusion lens of diameter 136 mm
- High luminous-efficiency glass reflector
- Fresnel lenses of diameter 200 mm
- Internal diffusion lens of diameter 136 mm

Electrical specification and connections

- Wiring options: EU model - 208/230/240V, 50/60Hz, US model - 100/120/208/230V, 50/60Hz
- Power consumption: 720VA at 230V/50Hz
- Wiring options: EU model - 208/230/240V, 50/60Hz, US model - 100/120/208/230V, 50/60Hz
- Power consumption: 720VA at 230V/50Hz

Mechanical specification

- Height: 588 mm (23.1") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")
- Height: 588 mm (23.1") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")

Thermal specification

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Maximum ambient temperature (Ta): 40°C (104°F)

- Maximum surface temperature: 80°C (176°F)

Control and programming

- Protocol: USITT DMX-512, RDM support
- Control channels: 16, 18, 19, 21
- DMX channels: 4 protocol modes
- Protocol: USITT DMX-512, RDM support
- Control channels: 16, 18, 19, 21
- DMX channels: 4 protocol modes

Electromechanical effects

- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%
- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%

Rigging

- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks
- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks

Optional accessories


- Module of front wide-angle lens D200 (87° angle)
- Remote Control IR
- Top Hats
- Module of front wide-angle lens D200 (87° angle)
- Remote Control IR
- Top Hats

Gobos&Colours

Colour Wheel




14070121



14070119



14070118



14070123



14070122