

# iESPRITE®

Make outdoor lighting complications and stress a thing of the past! Our no-compromise, self-maintaining, revolutionary iESPRITE® delivers consistent, hassle-free performance without complex maintenance procedures, whatever the weather or atmospheric conditions.

**Light source**

iSE-TE™ 650W White LED TRANSFERABLE ENGINE

**Light output**

34.000 lm, 85.000 lx @ 5m, Cpulse™ special flicker free management for HD and UHD cameras, ready for 8K and 16K

**Zoom range**

5.5° - 50°

**Effects**

Static and rotating gobo wheel, Animation wheel, Framing shutters, Prism



The IP65-rated iESPRITE® combines our latest protection technology with the highly desired ESPRITE® maintaining identical output and feature-rich effects in a fully protected package capable of handling all the challenges of outdoor environments.

Joining the Robe iSeries iESPRITE® again negates the traditional weight penalty associated with IP-rated fixtures having similar weight to the indoor ESPRITE®. With class-leading form factor, size and appearance, and all the features and identical performance of the indoor original, iESPRITE® once again enables seamless integration between models, even on the same truss if desired!

The ingenious ingress protection system has been specifically designed to allow standard maintenance and preparation procedures, such as TRANSFERABLE ENGINE exchange and gobo replacement, without any additional tools, as gobo changes or maintenance work can be done on-site. The onboard patented RAINS™ (Robe Automatic Ingress Neutralization System) manages humidity, temperature and pressure control using an active monitoring system that automatically removes any moisture detected within the fixture and provides constant monitoring to ensure peak performance.

iESPRITE® runs an ingenious Self Pressure Test to check internal pressure. This self-test, taking less than 3 minutes, provides an error message if gaskets and covers were not replaced correctly or locking screws were incorrectly tightened, ensuring maximum protection.

Their lightweight magnesium alloy covers, with aluminium alloy substructure, provide a dust-free environment for the optics. This eliminates the need for frequent cleaning, routine maintenance, and UV damage to plastic parts. To maintain consistently high lumen output, even with the rigours of outdoor performance, water, dirt, dust, haze, and smoke are repelled from the front lens with our unique parCoat™ hydrophobic, oleophobic-resistant coating. Furthermore, it allows easy removal of deposits without scratching or damage.

By including NFC (Near-Field Communication) technology, you can access setup, diagnostic and performance features, even when the fixture is not powered directly from your mobile device using the Robe Com app.

Outdoor fixtures need to operate in extreme cold. iESPRITE® contains an innovative POLAR+™ technology - a special standby mode with low power consumption, in which the fixture's sensors and communications channels continue to function. When activated, POLAR+™ automatically maintains an internal temperature level, giving instant operability down to minus 50 degrees centigrade!

iESPRITE® is available with a choice of patented IP65-rated iSE-TE™ 650W White LED TRANSFERABLE ENGINES; HP (High Performance) 6.700 K, 34.000 lm CRI70; HCF (High Colour Fidelity) 6.000 K, 22.800 lm CRI 96.

The identical 9:1 zoom optical system, with a 5.5° to 50° zoom range, provides all the flexibility you need. Our cutting-edge CMY colour mixing system provides beautifully smooth mixing and transitions. Combined with two colour wheels, CRI 80 and 90 filters (HP Engine), and a variable CTO from 3.000 - 6.700 K give iESPRITE® total colour finesse. With the patented Plano4™ four individual plane framing shutters; one rotating fully indexable and one static gobo wheel; an animation wheel; a 6-facet bi-directional variable speed prism and two MagFrost™ 1° and 5° frosts, you have all the creative tools you need. Removing the need for distracting pre-use pan and tilt calibration movement, our patented MAPS™ (Motionless Absolute Positioning System) allows the fixture to fully calibrate while remaining static. Very useful when located within confined spaces.

For those requiring maintained network connectivity, we have Epass™ available as standard. Our REAP™ (Robe Ethernet Access Portal) allows access to fixture information and diagnostics over Ethernet Networks. Perfect for installations requiring remote centralised monitoring of fixture performance. Important for television users, Cpulse™ provides flicker-free management of the latest camera systems.

iESPRITE® is fully compatible with our industry-leading RoboSpot™ remote-controlled follow-spot system.

**iESPRITE® - Robe reliability in all weathers.**

# Technical Specification

## Source

- Light source type: iSE-TE™ 650W HP White LED Engine (patented):
  - HP - High Performance Engine for maximum light output and optimal colour characteristics
  - LED Engine output: 55.000 lm
  - Fixture total lumen output:
    - 34.000 lm (integrating sphere)
    - 27.000 lm (goniophotometer)
  - Colour temperature output: 6.700 K
  - CRI: 70, remotely selectable filters for CRI 80 and CRI 90
  - Illuminance: 85.000 lx @ 5 m
- Light source type: iSE-TE™ 650W HCF White LED Engine (Patented):
- Light source type: iSE-TE™ 650W HP White LED Engine (patented):
  - HP - High Performance Engine for maximum light output and optimal colour characteristics
  - LED Engine output: 55.000 lm
  - Fixture total lumen output:
    - 34.000 lm (integrating sphere)
    - 27.000 lm (goniophotometer)
  - Colour temperature output: 6.700 K
  - CRI: 70, remotely selectable filters for CRI 80 and CRI 90
  - Illuminance: 85.000 lx @ 5 m
- Light source type: iSE-TE™ 650W HCF White LED Engine (Patented):

## Optical system

- Robe's proprietary optical design
- High-efficiency 13-lens zoom optical system, ratio: 9:1
- Zoom range: 5.5° - 50°
- Robe's proprietary optical design
- High-efficiency 13-lens zoom optical system, ratio: 9:1
- Zoom range: 5.5° - 50°

## Dynamic Effects and Features

- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%
- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%

## Control and programming

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding, NFC app controller
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding, NFC app controller
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN

## Movement

- Pan movement: 540°
- Tilt movement: 265°
- Movement control: Standard and Speed
- Pan movement: 540°
- Tilt movement: 265°
- Movement control: Standard and Speed

## Rotating gobos

- 7x rotating glass gobos
- Outside diameter: 26.8 mm
- Image diameter: 23.5 mm
- 7x rotating glass gobos
- Outside diameter: 26.8 mm
- Image diameter: 23.5 mm

## Static gobos

- 9x static glass gobos
- Outside diameter: 26.8 mm
- Image diameter: 23.5 mm
- 9x static glass gobos
- Outside diameter: 26.8 mm
- Image diameter: 23.5 mm

## Effect wheel

- Single animation wheel
- Material: Aluminium
- Can be used alone or in combination with rotating gobos
- Single animation wheel
- Material: Aluminium
- Can be used alone or in combination with rotating gobos

## Framing shutters system

- Patented Plano4™ framing shutters module
- Shutters: 4 Blades, each with separate movement and +- 25° rotation control
- Movement: Smooth with variable speed, ultrafast blade movements for creating mid-air effects
- Patented Plano4™ framing shutters module
- Shutters: 4 Blades, each with separate movement and +- 25° rotation control
- Movement: Smooth with variable speed, ultrafast blade movements for creating mid-air effects

## Thermal specification

- Maximum ambient temperature: 50°C (122°F)
- Maximum surface temperature: 80°C (176°F)
- Minimum operating temperature: -50°C (-58°F)
- Maximum ambient temperature: 50°C (122°F)
- Maximum surface temperature: 80°C (176°F)
- Minimum operating temperature: -50°C (-58°F)

## Noise Levels

- Sound pressure level:
  - 27 dB(A) at 1 m (quiet mode)
  - 42 dB(A) at 1 m (auto mode)
- Sound power level:
- Sound pressure level:
  - 27 dB(A) at 1 m (quiet mode)
  - 42 dB(A) at 1 m (auto mode)
- Sound power level:

## Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption:
- Power supply: Electronic auto-ranging
- Input voltage range: 100-240 V, 50/60 Hz
- Power consumption:

## Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

## Mechanical specification

- Height: 756 mm (29.76") - head in vertical position
- Width: 458 mm (18.03")
- Depth: 289 mm (11.37") - head in vertical position
- Height: 756 mm (29.76") - head in vertical position
- Width: 458 mm (18.03")
- Depth: 289 mm (11.37") - head in vertical position

## Rigging

- Mounting positions: 0°, 90°
- Universal operating position
- Mounting points: 5 pairs of 1/4-turn locking points

- Mounting positions: 0°, 90°
- Universal operating position
- Mounting points: 5 pairs of 1/4-turn locking points

## Included items

- User Manual
- Omega Adaptor CL-regular 2 pcs: 10980033
- Power cord including powerCON TRUE1 In connector:
- User Manual
- Omega Adaptor CL-regular 2 pcs: 10980033
- Power cord including powerCON TRUE1 In connector:

## Optional accessories

- iESPRITE iSE-TE™ 650W HP White LED Engine: 14080086
- iESPRITE iSE-TE™ 650W HCF White LED Engine: 14080087
- Frost 0.5° (exchange) assembled: 10980583
- iESPRITE iSE-TE™ 650W HP White LED Engine: 14080086
- iESPRITE iSE-TE™ 650W HCF White LED Engine: 14080087
- Frost 0.5° (exchange) assembled: 10980583

## Legal

- iESPRITE® is Registered Trademark of Robe lighting s. r. o.
- iESPRITE® is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents
- iESPRITE® is Registered Trademark of Robe lighting s. r. o.
- iESPRITE® is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents

# Gobos&Colours

## Rotating Gobo Wheel



15020372



15020373




15020374




15020375



15020376



15020377



15040011

## Static Gobo Wheel



15020378



15020379



15020380



15020381



15020382



15020383



15020384




15020385



15020386

## Colour Wheel 1



14070463




14070464



14070465



14070466



14070467


## Colour Wheel 2




14070473-6




14070469



14070470



14070471




14070472

## Animation Wheel







11020208-02