

MolyPATT™

Add retro style to your next broadcast, corporate event, stage or film set with the latest edition to the PATT family, designed to give a classic warm tungsten glow with a twist of modern edge.

**Light source**

Tungsten LED bulb

**Effects**

353mm see through parabolic aluminium reflector with gold-brown coating



Again, taking inspiration from vintage broadcast luminaires, let the MolyPATT™ add gorgeous scenic elements to your show. With a timeless brushed aluminium finish, these fixtures are the perfect scenic element for set dressing or ambience.

Based on the picklePATT™, the smaller MolyPATT™ features a 4W LED Vintage Soft Coil filament lamp with a colour temperature of 1.800 K to illuminate the see-through gold-brown parabolic reflector, producing a warm, atmospheric glow.

Silent in operation due to convection cooling, their ultra-smooth dimming makes them the ideal complement to any setting.

Let the MolyPATT™ add warmth and enhanced visual appeal to your life and sets!

Technical Specification

Source

- Light source type: Tungsten LED bulb
- Base: E27
- Recommended lamp type: Bell 60019 LED Vintage soft coil filament 95 mm Globe ES Cap 4W
- Light source type: Tungsten LED bulb
- Base: E27
- Recommended lamp type: Bell 60019 LED Vintage soft coil filament 95 mm Globe ES Cap 4W

Optical system

- 353mm see through parabolic aluminium reflector with gold-brown coating
- 353mm see through parabolic aluminium reflector with gold-brown coating

Control and programming

- External Dimmer
- External Dimmer

Thermal specification

- Maximum ambient temperature: 45°C (113°F)
- Maximum surface temperature: 160°C (320°F)
- Maximum ambient temperature: 45°C (113°F)
- Maximum surface temperature: 160°C (320°F)

Electrical specification and connections

- Input voltage range: 120 V or 240 V, 50/60 Hz
- Power consumption: 4 W
- Input voltage range: 120 V or 240 V, 50/60 Hz
- Power consumption: 4 W

Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

Mechanical specification

- Height: 520 mm (20.5")
- Width: 532 mm (21")
- Depth: 159 mm (6.3")
- Height: 520 mm (20.5")
- Width: 532 mm (21")
- Depth: 159 mm (6.3")

Rigging

- Mounting points: M12 mounting for clamp or spigot
- Universal operating position
- Mounting points: M12 mounting for clamp or spigot
- Universal operating position

Included items

- User Manual
- Power cord
- User Manual
- Power cord

Optional accessories

- Single Top Loader Case: 10120338
- Dual Top Loader Case: 10120339
- Quad Top Loader Case: 10120340
- Single Top Loader Case: 10120338
- Dual Top Loader Case: 10120339
- Quad Top Loader Case: 10120340

Legal

- MolyPATT™ is a Trademark of Robe lighting s. r. o.
- MolyPATT™ is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents
- MolyPATT™ is a Trademark of Robe lighting s. r. o.
- MolyPATT™ is patented by Robe lighting s. r. o. and protected by one or more pending or issued patents