

# BMFL™ Spot

The BMFL™ – Bright Multi-Functional Luminaire – much anticipated new lighting fixture from Robe, brings a real game changer in the world of moving lights.

**Light source**

1700 W OSRAM Lok-it! HTI 1700/PS

**Light output**

40.000 lm, 250.000 lx @ 5 m, 2.500 lx @ 50 m

**Zoom range**

5° - 55°

**Effects**

2x gobo wheel, dual graphic wheel, circular and linear prism



The BMFL Spot™ has a custom light source designed for Robe and produces a staggering powerful 250 000 lux at 5 metres – no other product currently on the market can equal this output! Despite its power and comprehensive feature set, it weighs just 36 Kgs... and has a compact body profile.

The lamp produces light at a CRI of 92+, this combined with a refined optical system, 5-55 degree zoom, results in a crisp, high quality fat beam that is truly homogenised and without a hotspot. There are also two colour wheels which include filters that can be utilised to adjust colour temperature and improve the CRI of the white output in aging lamps. There are two rotating gobo wheels – each with six slot&lock gobo positions. There are also two Rotating Prisms. The Dual Graphic Wheels both focus within the same focal plane and the rotation and movement can be individually controlled and varied... to create ultra-cool, infinitely subtle special effects. The frost and dimming functions provide further effects.

Three grades of Frost are available and the dimmer is exceptionally smooth with no distortion, so the full beam width is visible right up to the point at which it disappears. The strobe effect is authentic with up to 10 flashes per second!

Aimed at long-throw applications, the newly patented Robe EMS™ (Electronic Motion Stabiliser) technology, enables the BMFL™ to absorb vibrations from audio outputs, truss movement, sprung or suspended floors, etc. The BMFL™ is a very powerful, feature packed luminaire that will provide a real signature light source for any project.

# Technical Specification

## Source

- Lamp: Compact short-arc metal halide lamp
- Base: PGJX28
- Approved model: OSRAM Lok-it! HTI 1700/PS
- Lamp: Compact short-arc metal halide lamp
- Base: PGJX28
- Approved model: OSRAM Lok-it! HTI 1700/PS

## Optical system

- Robe's proprietary optical design
- High - efficiency zoom optical system, ratio 11:1
- Zoom range: 5°-55°
- Robe's proprietary optical design
- High - efficiency zoom optical system, ratio 11:1
- Zoom range: 5°-55°

## Dynamic Effects and Features

- Cyan: 0 - 100 %
- Magenta: 0 - 100 %
- Yellow: 0 - 100 %
- Cyan: 0 - 100 %
- Magenta: 0 - 100 %
- Yellow: 0 - 100 %

## Control and programming

- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Setting & Addressing: ROBE Navigation System 2 (RNS2)
- Display: QVGA Robe touch screen with battery backup, gravitation sensor for auto screen positioning, operation memory service log with RTC, stand-alone operation with 3 editable programs (each up to 100 steps), built-in analyser for easy fault finding
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN

## Movement

- Pan movement: 540°
- Tilt movement: 270°
- Movement control: Standard and Speed
- Pan movement: 540°
- Tilt movement: 270°
- Movement control: Standard and Speed

## Rotating gobos

- 12x fully rotating, indexable glass gobos on two wheels
- Outside diameter: 30.8 mm
- Image diameter: 25.0 mm
- 12x fully rotating, indexable glass gobos on two wheels
- Outside diameter: 30.8 mm
- Image diameter: 25.0 mm

## Effect wheel

- Dual Graphic Wheel
- Material: Aluminium
- Diameter: 96 mm
- Dual Graphic Wheel
- Material: Aluminium
- Diameter: 96 mm

## Thermal specification

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 100 °C (212 °F)
- Minimum operating temperature: -5°C (23°F)
- Maximum ambient temperature: 45 °C (113 °F)
- Maximum surface temperature: 100 °C (212 °F)
- Minimum operating temperature: -5°C (23°F)

## Electrical specification and connections

- Power supply: Electronic auto-ranging
- Input voltage range: 200-240 V, 50/60 Hz
- Power consumption: 2000 W at 230 V / 50 Hz
- Power supply: Electronic auto-ranging

- Input voltage range: 200-240 V, 50/60 Hz
- Power consumption: 2000 W at 230 V / 50 Hz

## Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

## Mechanical specification

- Height: 813 mm (32") - head in vertical position
- Width: 483 mm (19")
- Depth: 335 mm (13.2")
- Height: 813 mm (32") - head in vertical position
- Width: 483 mm (19")
- Depth: 335 mm (13.2")

## Rigging

- Mounting positions: 0°, 32° and 90°
- Universal operating position
- Mounting points: 5 pairs of 1/4-turn locking points
- Mounting positions: 0°, 32° and 90°
- Universal operating position
- Mounting points: 5 pairs of 1/4-turn locking points

## Included items

- User Manual
- Omega Adaptor CL-regular 2 pcs
- Power cord including powerCON In connector
- User Manual
- Omega Adaptor CL-regular 2 pcs
- Power cord including powerCON In connector

## Optional accessories

- Lamp Osram Lok-it HTI 1700/PS: 14080049
- BMFL Handles - 2 pcs in box: 10980233
- BMFL Side Handle: 10980396
- Lamp Osram Lok-it HTI 1700/PS: 14080049

- BMFL Handles - 2 pcs in box: 10980233
- BMFL Side Handle: 10980396

## Legal

- BMFL™ is a trademark of Robe lighting s.r.o.
- BMFL™ Spot is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patent
- BMFL™ is a trademark of Robe lighting s.r.o.
- BMFL™ Spot is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patent

## Gobos&Colours

### Rotating Gobo Wheel 1



15020290



15020291



15020292



15020293




15020294




15020295


### Rotating Gobo Wheel 2




15020296



15020298



15020299



15020300




15020297



15020301

### Colour Wheel 1



14070411



14070393




14070394



14070395




14070396



14070397

### Colour Wheel 2



99014263




99014264




99014265



99014266




99014267




99014268

### Animation Wheels



11020171



11020172