

# ColorWash 575E AT Zoom™

The ColorWash 575E AT Zoom is an electronic ballast version of ColorWash 575 AT Zoom, which provides flicker-free operation. The fixture offers an extremely smooth linear motorized zoom that ranges from 8° to 50°. Thanks to the zoom this fixture is ideal for all types of professional installations.



# Technical Specification

## Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2
- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved model: Philips MSR 575/2

## Optical system

- High luminous-efficiency glass reflector
- Fresnel lenses of diameter 200 mm
- High luminous-efficiency glass reflector
- Fresnel lenses of diameter 200 mm

## Electrical specification and connections

- Wiring options: 100/120/208/230/240V, 50/60Hz
- Power consumption: 720VA at 230V/50Hz
- Wiring options: 100/120/208/230/240V, 50/60Hz
- Power consumption: 720VA at 230V/50Hz

## Mechanical specification

- Height: 588 mm (23.1") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")
- Height: 588 mm (23.1") - head in horizontal position
- Width: 470 mm (18.5")
- Depth: 446 mm (17.6")

## Thermal specification

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Internal diffusion lens of diameter 136 mm
- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

- Internal diffusion lens of diameter 136 mm

## Control and programming

- Protocol: USITT DMX-512, RDM support
- Control channels: 16, 18, 19, 21
- DMX channels: 4 protocol modes
- Protocol: USITT DMX-512, RDM support
- Control channels: 16, 18, 19, 21
- DMX channels: 4 protocol modes

## Electromechanical effects

- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%
- Cyan: 0 - 100%
- Magenta: 0 - 100%
- Yellow: 0 - 100%

## Rigging

- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks
- Mounting points: 4 pairs of ¼-turn locks
- 2x Omega bracket with ¼-turn quick locks

## Optional accessories

- Module of Front wide-angle lens D200 (87° angle)
- Top Hats
- Module of Front wide-angle lens D200 (87° angle)
- Top Hats