

# Spot 150 XT

NO INTRO INCLUDED



# Technical Specification

## Source

- Lamp: Compact discharge lamp
- Base: G-12
- Approved model: Philips CDM-SA/T 150/942
- Lamp: Compact discharge lamp
- Base: G-12
- Approved model: Philips CDM-SA/T 150/942

## Optical system

- Objective: 19°
- Objective: 19°

## Electrical specification and connections

- Wiring options - EU-model: 208/230/240V AC, 50/60Hz
- Wiring options - US model: 100/120/208/230/240V AC,50/60Hz
- Power consumption: 300 VA at 230V/50Hz
- Wiring options - EU-model: 208/230/240V AC, 50/60Hz
- Wiring options - US model: 100/120/208/230/240V AC,50/60Hz
- Power consumption: 300 VA at 230V/50Hz

## Mechanical specification

- Height: 415 mm (16.3") - head in horizontal position
- Width: 292 mm (11.5")
- Depth: 378 mm (14.9")
- Height: 415 mm (16.3") - head in horizontal position
- Width: 292 mm (11.5")
- Depth: 378 mm (14.9")

## Thermal specification

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

## Rotating gobos

- Outside diameter: 26.9 mm, aluminium, thickness: 0.5 mm
- Outside diameter: 26.9 mm, aluminium, thickness: 0.5 mm

## Control and programming

- Protocol: USITT DMX-512
- Control channels: 8
- Bilt-in demo sequences
- Protocol: USITT DMX-512
- Control channels: 8
- Bilt-in demo sequences

## Electromechanical effects

- Colour wheel: 11 dichroic filters + open
- Static gobo wheel: 11 metal gobos + open
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Colour wheel: 11 dichroic filters + open
- Static gobo wheel: 11 metal gobos + open
- Dimmer/Shutter: Full range dimming and variable strobe effect

## Rigging

- via 2 Omega holders
- via 2 Omega holders