

# RecessedWash 150 AT

RecessedWash 150 AT is ideal for architectural lighting, bars, restaurants, clubs, retail stores, churches, exhibit halls and for all other ceiling-mount applications. The RecessedWash 150 is a ceiling-mount version of Wash 150 XT with all functions of the popular Wash 150 XT moving head. Its colour wheel offers 10 dichroic slots plus open, and it has a dimmer and shutter. It uses a 150 Watt CDM lightsource from Philips.



# Technical Specification

## Source

- Lamp: Compact discharge lamp
- Base: G-12
- Approved model: Philips CDM-SA/T 150/942
- Lamp: Compact discharge lamp
- Base: G-12
- Approved model: Philips CDM-SA/T 150/942

## Optical system

- 21° beam angle
- 21° beam angle

## Electrical specification and connections

- Wiring options - EU - model: 208/230/240V AC, 50/60Hz, Wiring options - US - model: 100/120/208/230/240V AC, 50/60Hz
- Power consumption: 300 VA at 230V/50Hz
- Wiring options - EU - model: 208/230/240V AC, 50/60Hz, Wiring options - US - model: 100/120/208/230/240V AC, 50/60Hz
- Power consumption: 300 VA at 230V/50Hz

## Mechanical specification

- Height (including ceiling box): 410 mm (16.1") - head in horizontal position
- Width (including ceiling box): 595 mm (23.4")
- Depth (including ceiling box): 593 mm (23.3")
- Height (including ceiling box): 410 mm (16.1") - head in horizontal position
- Width (including ceiling box): 595 mm (23.4")
- Depth (including ceiling box): 593 mm (23.3")

## Thermal specification

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)
- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

## Control and programming

- Protocol: USITT DMX-512
- Control channels: 6 - 8 DMX, 4 protocol modes
- Built-in demo sequences
- Protocol: USITT DMX-512
- Control channels: 6 - 8 DMX, 4 protocol modes
- Built-in demo sequences

## Electromechanical effects

- Colour wheel: 11 dichroic filters + open
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Pan: 530°
- Colour wheel: 11 dichroic filters + open
- Dimmer/Shutter: Full range dimming and variable strobe effect
- Pan: 530°

## Rigging

- Ceiling box for 600x600 mm grid mounting
- Integral attachment points for wire hangers or all-thread support
- Ceiling box for 600x600 mm grid mounting
- Integral attachment points for wire hangers or all-thread support