

# REDBlinder 2•48™

The REDBlinder 2•48 is a 4-way version of the REDBlinder 2•96. The unit is fitted into the industry standard 4-lite casing and offers set and lighting designers all the options. It has 4 LED modules, each with 12 RGB K2 LEDs. Each two pairs of modules are separately controllable. This product is aimed at all stage lighting markets and television productions and for arenas and larger venues.



# Technical Specification

## Source

- High-Power Luxeon K2 LEDs
- 16 Red K2 LEDs, 16 Green K2 LEDs, 16 Blue K2 LEDs
- Min. 50.000 hrs Rated Life
- High-Power Luxeon K2 LEDs
- 16 Red K2 LEDs, 16 Green K2 LEDs, 16 Blue K2 LEDs
- Min. 50.000 hrs Rated Life

## Beam angle

- 25° beam angle of each LED
- 25° beam angle of each LED

## Frost, diffusion

- Optional frost filters (glass or film) for even light distribution
- Optional frost filters (glass or film) for even light distribution

## Colours

- 16.7 million colours (24 bit)
- Pre-programmed colours & rainbow effect
- Dynamic colour balance between white and red, green, blue colours during production
- 16.7 million colours (24 bit)
- Pre-programmed colours & rainbow effect
- Dynamic colour balance between white and red, green, blue colours during production

## Dimmer, Strobe

- Electronic dimmer for light output adjustment from 0 to 100%
- High speed white or full colour strobe, flash rate 1-25 fps
- Electronic dimmer for light output adjustment from 0 to 100%
- High speed white or full colour strobe, flash rate 1-25 fps

## Mechanical specification

- Height: 510 mm (20.0")
- Width: 480 mm (18.9")
- Depth: 190 mm (7.5")

- Height: 510 mm (20.0")
- Width: 480 mm (18.9")
- Depth: 190 mm (7.5")

## Thermal specification

- Maximum ambient temperature: 40°C (104°F)
- Maximum housing temperature: 80°C (176°F)
- Maximum ambient temperature: 40°C (104°F)
- Maximum housing temperature: 80°C (176°F)

## Control and programming

- Protocol: USITT DMX-512
- Control options: DMX, Auto-trigger
- Operation modes: Master/Slave, Stand-alone
- Protocol: USITT DMX-512
- Control options: DMX, Auto-trigger
- Operation modes: Master/Slave, Stand-alone

## DMX channels

- Mode 1: 9 channels
- Mode 2: 6 channels
- Mode 3: 6 channels
- Mode 1: 9 channels
- Mode 2: 6 channels
- Mode 3: 6 channels

## Connection

- Control: DMX 512
- DMX connection: 3-pin or 5-pin XLR-sockets
- Control: DMX 512
- DMX connection: 3-pin or 5-pin XLR-sockets

## Power consumption

- Input Voltage: 100-240 V, 50/60 Hz
- Max. Power Consumption: 135 VA
- Input Voltage: 100-240 V, 50/60 Hz
- Max. Power Consumption: 135 VA

**Optional accessories**

- Set glass frost
- Set film frost
- Set glass frost
- Set film frost