

# MediaSpinner 100 AT™

NO INTRO INCLUDED



# Technical Specification

## Power consumption

- Wiring options: EU-model - 208/230/240 V AC, 50/60 Hz ~, US-model - 100/120/208/230/240 V AC, 50/60 Hz ~
- Power consumption: 30 VA
- Wiring options: EU-model - 208/230/240 V AC, 50/60 Hz ~, US-model - 100/120/208/230/240 V AC, 50/60 Hz ~
- Power consumption: 30 VA

## Electronics

- Addressing, special functions setting via control panel with 4-digit LED display
- Readout fixture usage, receiving DMX values, temperature, etc.
- Built-in analyzer for easy fault finding, error messages
- Addressing, special functions setting via control panel with 4-digit LED display
- Readout fixture usage, receiving DMX values, temperature, etc.
- Built-in analyzer for easy fault finding, error messages

## Data input/output

- base:
- 3-pin/5-pin XLR male sockets for DMX data input
- 3-pin/ 5-pin XLR female sockets for DMX data output
- base:
- 3-pin/5-pin XLR male sockets for DMX data input
- 3-pin/ 5-pin XLR female sockets for DMX data output

## Pan

- Pan movement range 450°
- 16-bit movement resolution
- Automatic pan position correction
- Pan movement range 450°
- 16-bit movement resolution
- Automatic pan position correction

## Rigging

- Standing directly on the floor
- Mounting horizontally with 2 Omega brackets
- Safety chain/cord attachment point

- Standing directly on the floor
- Mounting horizontally with 2 Omega brackets
- Safety chain/cord attachment point

**Load specification**

- Max. load: 100 kg
- Max. current for load: 16 A
- Max.ambient temperature: 40 °C
- Max. load: 100 kg
- Max. current for load: 16 A
- Max.ambient temperature: 40 °C