



Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

DMX Control 512™

The DMX Control 512 offers control of up to 16 fixtures with a maximum of 32 channels each.



The DMX Control 512 supports ROBE and all other popular lighting brands. A show of up to 1024 Scenes can be created consisting of Presets and Chases. The DMX Control 512 uses Flash memory for easy software updates via a computer (RS 232). The DMX Control 512 is suitable for all range of AT, CT and LT series.



ROBE lighting s .r. o., Hazovice 2090 75661 Roznov pod Radhostem Czech Republic Tel: +420-571-751500 Fax: +420-571-751515 Email: info@robe.cz

Technical Specification

Control and programming

- Real time control of Moving Heads and Scanners
- Total 512 DMX Channels
- Control 16 Projectors up to 32 channels each
- Real time control of Moving Heads and Scanners
- Total 512 DMX Channels
- Control 16 Projectors up to 32 channels each

Electrical specification

- Power supply: 120/230V via external Power Supply 9V DC/500mA
- Power supply: 120/230V via external Power Supply 9V DC/500mA

Mechanical specification

- Height: 120 mm (47.2")
- Width: 133 mm (52.4")
- Length: 483 mm (19.0")
- Height: 120 mm (47.2")
- Width: 133 mm (52.4")
- Length: 483 mm (19.0")

Rigging

- Rack size: 19" 3U rack mountable, 3 spaces
- Rack size: 19" 3U rack mountable, 3 spaces