

# Strobe™ / Strobe Lite™

Power is everything! The Strobe from Robe could not be anything but THE brightest, best value, most sophisticated strobe-blinder effects unit on the market.

**Light source**

120x High Power White LED chips

**Light output**

5.600 lux @ 5 m / 48.500 lm

**Effects**

12 zones control, continuous full power operation, strobe effects



Ultimately controllable, configurable and arrayable. Super fast bursts of high powered pulses can be adjusted in frequency, duration and intensity, optically harnessed from the 120x High Power White LED chips. Easy to rig individually or in multiples and easy to program, using direct segment control or the pre-defined macros. Fitted with the standard Robe RNS touch screen system with DMX, RDM, Art-Net, MA Net and sACN protocols. Optional wireless DMX module.

# Technical Specification

## Source

- Light Source Type: 120x High Power White LED chips
- CCT: 6.000 K
- LED Life Expectancy: Minimum 60 000 hours
- Light Source Type: 120x High Power White LED chips
- CCT: 6.000 K
- LED Life Expectancy: Minimum 60 000 hours

## Optical system and effects

- High efficient component optics
- Beam Angle: 32° (at 1/2 beam), 60° (at 1/10 beam)
- Individual control: 12 segments (3 lines and 4 columns)
- High efficient component optics
- Beam Angle: 32° (at 1/2 beam), 60° (at 1/10 beam)
- Individual control: 12 segments (3 lines and 4 columns)

## Control and programming

- Setting & Addressing: Robe Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Optional wireless version available: CRMX™ technology from Lumen Radio
- Setting & Addressing: Robe Navigation System 2 (RNS2)
- Protocols: USITT DMX-512, RDM, ArtNet, MA Net, MA Net2, sACN
- Optional wireless version available: CRMX™ technology from Lumen Radio

## Thermal specification

- Maximum Ambient Temperature: 45° C (113° F)
- Maximum Housing Temperature: 75° C (167° C)
- Maximum Ambient Temperature: 45° C (113° F)
- Maximum Housing Temperature: 75° C (167° C)

## Movement

- Tilt adjustment: Manual
- Tilt adjustment: Manual

## Electrical specification

- Electronic auto-ranging
- Input Voltage Range: 100-240 V, 50/60 Hz
- Power Consumption: 660 W
- Electronic auto-ranging
- Input Voltage Range: 100-240 V, 50/60 Hz
- Power Consumption: 660 W

## Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

## Mechanical specification

- Height (U-holder vertically): 350 mm (13.8")
- Width: 315 mm (12.4")
- Depth: 300 mm (11,8")
- Height (U-holder vertically): 350 mm (13.8")
- Width: 315 mm (12.4")
- Depth: 300 mm (11,8")

## Rigging

- Mounting Points: 1 pair of 1-turn locks
- Multipoint segment locking for big trusses instalations
- Omega Brackets: 2x Omega bracket with 1-turn quick locks
- Mounting Points: 1 pair of 1-turn locks
- Multipoint segment locking for big trusses instalations
- Omega Brackets: 2x Omega bracket with 1-turn quick locks

## Optional accessories

- Optional: floor stand, barndoor, frame adaptor, gel frame, stacker
- Optional: floor stand, barndoor, frame adaptor, gel frame, stacker