

Actor 3 ST™

The Actor ST range of wash luminaires bring all the advantages of the award winning ROBIN® LEDWash series to the fixed position application.

**Light source**

19x 15W RGBW LED multichips

**Light output**

1.710 lux @ 5 m / 2.954 lm

**Zoom range**

8° - 63°

**Effects**

3 LED rings control, rainbow effects, tungsten lamp effect, pre-programmed whites



The LEDWash 300 and 600 models have been reverse engineered to deliver even smaller, easy to control static heads that can be manually locked into position. High power 15w RGBW LED's are incorporated into the Robe patented motorised zoom optic system which provides a smooth, flat progressive beam from a tight 8 degree right out to an impressive 63 degrees. There is full DMX control over the zoom angle, colour mixing - including the 237 pre-set colours, selectable whites, variable CTO and concentric ring effect macros. The tungsten emulation function allow the fixtures to be integrated seamlessly into lighting schemes with existing traditional lanterns. The extremely low overall cost-of-ownership - driven by the 60,000 hour LED life expectancy, makes the Actor range the only choice for controllable wash lighting static stage and studio installations.

Technical Specification

Source

- Light source: 19x 15W RGBW LED multichips
- Led Life Expectancy: > 60.000 hours
- Typical Lumen Maintenance: 70% @ 60.000 hours
- Light source: 19x 15W RGBW LED multichips
- Led Life Expectancy: > 60.000 hours
- Typical Lumen Maintenance: 70% @ 60.000 hours

Optical system and effects

- High efficiency component optics
- Linear motorized zoom: 8–63°
- Color mixing: RGBW/CMY, 8 or 16 bit
- High efficiency component optics
- Linear motorized zoom: 8–63°
- Color mixing: RGBW/CMY, 8 or 16 bit

Control and programming

- User Interface: Colour Touch Screen
- Protocols: USITT DMX 512, RDM
- Pan and Tilt, range: 450°/300°
- User Interface: Colour Touch Screen
- Protocols: USITT DMX 512, RDM
- Pan and Tilt, range: 450°/300°

Thermal specification

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)
- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)

Electrical specification

- Supply Input: 100–240 V AC, 50–60 Hz auto ranging
- Power consumption: 200 W
- Power connection: Neutrik PowerCon (Power cable supplied)

- Supply Input: 100-240 V AC, 50-60 Hz auto ranging
- Power consumption: 200 W
- Power connection: Neutrik PowerCon (Power cable supplied)

Mechanical specification

- Height: 328 mm (12,9")
- Width: 295 mm (11.6")
- Depth: 154 mm (6.1")
- Height: 328 mm (12,9")
- Width: 295 mm (11.6")
- Depth: 154 mm (6.1")

Rigging

- Omega brackets: 1x (included) with ¼-turn quick locks
- Removable floor stand (included)
- Manual Tilt adjustment & lock
- Omega brackets: 1x (included) with ¼-turn quick locks
- Removable floor stand (included)
- Manual Tilt adjustment & lock

Optional accessories

- Top Hat for Adaptor
- Adaptor ring for barndoor / diffuser
- Barn Door
- Top Hat for Adaptor
- Adaptor ring for barndoor / diffuser
- Barn Door