

# LEDBeam 100 DL™

These 'Pure White' versions of the popular LEDBeam 100 fixture have been added to compliment the range of Pure White LEDWash products.



## Light source

12x 15W 6.500K multichips



## Light output

11.620 lux @ 5 m



## Zoom range

7°



## Effects

strobe effects, diffusion filters



The LEDBeam utilises 12 x 15 W LEDs to provide an extra punchy 7 degree beam or with the addition of the clip on 25 or 40 degree frost filter, a flat, smooth wash. Small enough to 'hide' within a set, the LEDBeam 100 is ideal for use on exhibitions or in retail environments where a powerful, quality light is required with the added benefits of low power consumption and no lamp replacement or maintenance cost. The motorised Pan and Tilt system is equally capable of dramatic fast movement as it is a subtle slow sweep. The DL model is fixed at 6500 K Available only on request.

# Technical Specification

## Source

- Light source: 12 x 15 W DayLight LED multichips
- Life Expectancy: > 60.000 hours
- Typical Lumen Maintenance: 70% @ 60.000 hours
- Light source: 12 x 15 W DayLight LED multichips
- Life Expectancy: > 60.000 hours
- Typical Lumen Maintenance: 70% @ 60.000 hours

## Optical system and effects

- High efficiency component optics
- Beam angle 7°
- White colour temperature: 6500 K
- High efficiency component optics
- Beam angle 7°
- White colour temperature: 6500 K

## Control and programming

- User Interface: 2 line LCD display & 4 push buttons
- Protocols: USITT DMX-512, RDM
- DMX modes (channels): 6 (16, 10, 12, 9, 16, 18)
- User Interface: 2 line LCD display & 4 push buttons
- Protocols: USITT DMX-512, RDM
- DMX modes (channels): 6 (16, 10, 12, 9, 16, 18)

## Thermal specification

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)
- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)

## Electrical specification

- Supply Input: 100–240 V AC, 50–60 Hz auto ranging
- Power consumption: 200 W max.
- Power connection: Neutrik PowerCon In/Out

- Supply Input: 100–240 V AC, 50–60 Hz auto ranging
- Power consumption: 200 W max.
- Power connection: Neutrik PowerCon In/Out

## Approvals

- CE Compliant
- cETLus Compliant
- CE Compliant
- cETLus Compliant

## Mechanical specification

- Height: 314 mm (12.4")
- Width: 233 mm (9.2")
- Depth: 149 mm (5.9")
- Height: 314 mm (12.4")
- Width: 233 mm (9.2")
- Depth: 149 mm (5.9")

## Rigging

- 1 x Omega bracket (included) with ¼-turn quick locks
- 1 x Omega bracket (included) with ¼-turn quick locks

## Optional accessories

- Top hat
- Diffusion filter 20°
- Diffusion filter 40°
- Top hat
- Diffusion filter 20°
- Diffusion filter 40°